



**Inceptor® .300 AAC Blackout SRR™**  
Sport Utility Ammo™



**Technical Data**

Caliber	.300 AAC Blackout
Bullet Diameter (inches)	.308"
Bullet Type	Injection-Molded
Bullet Material	Copper-Polymer
Bullet Weight	88 gr (5.7 grams)
Case Material	Factory Brass
Primer	Small Rifle Primer
	Boxer

**Ballistic Data**

Velocity	2550 ft/s (± 25)
	777 m/s (± 8)
Bullet Energy	1271 ft/lbs (1723J)

	MUZZLE	25 YARDS	50 YARDS	75 YARDS	100 YARDS
VELOCITY (FPS)	2550	2403	2262	2125	1993
ENERGY (FT.LBS)	1271	1128	999	882	776
TRAJECTORY (Inches)	-2	-0.8	0	0.4	0.3



**Copper- Polymer Matrix Projectile**

- HIGH VELOCITY
- OPTIMIZED FOR 50-YARD PERFORMANCE
- LEAD-FREE
- STEELSAFE™ UNMATCHED FRANGIBILITY \*

\* Frangibility Test conducted in accordance with U.S. Federal Law Enforcement Training Standards (when fired against a vertical 3/8"x24"x24" armor steel plate (AR 400 Brinell or harder) at a 45 degree angle of impact, from a distance of 21 feet, shall fragment after a single impact, with the largest resulting fragment not exceeding 5 grains in weight and no 5 grain particle (or larger) shall penetrate a 200 weight cardboard witness panel located 21 feet from initial impact).

